

Manufactured from 1.2mm thick grade 304, satin polished stainless steel, with polished end panels (suitable for wall or exposed installation), 38mm white plastic domed waste outlet (in a left, right or central position), white high impact polystyrene cistern and all necessary pipework, clips and fixings, unless ordered otherwise. Available in any length, up to 3000mm, allowing approximately 600mm per person. For lengths in excess of 3000mm or for corner installations, two or more separate urinals should be used, each with their own waste and cistern. Bowl urinals are supplied in ranges of one to six.

There are two types of flushing arrangements:

- 1/ Top inlet (TI) square spargepipe with exposed cistern.
- 2/ Back inlet (BI) spreaders with concealed cistern.



U01 - Wall Mounted Trough Urinal
230mm wide x 460/600mm high



U03 - Floor-recessed Slab Urinal
350mm wide x 1050mm high



W1101 - White plastic domed waste 38mm dia.



U04 - Floor-standing Slab Urinal
350mm wide x 1050mm high

Optional



W1102 - CP brass domed waste 50mm dia.



U05 - Floor-standing Trough Urinal
350mm wide x 1050mm high



U06 - Standard Bowl Urinal
300x230x500mm high



W1101BS - Stainless steel domed brass waste 38mm dia.
W1101PS - Stainless steel domed plastic waste 38mm dia.



U06 - Circular Bowl Urinal
350x390x460mm high

Please note that all urinal spargepipes, spreaders, wastes and fittings are available to order separately.

Optional Extras

- J0795** - Joint cover trim
- C0796** - Corner capping (slab urinal)
- C0797** - Corner capping (wall urinal)

- T0000** - Trap Shroud
- C0798** - Stainless steel automatic cistern
- D0796** - Downpipe Shroud